

Diaphragm type compressors / Vacuum pumps

- CRP - Chemically resistive parts
- DC - Dc motor
- FM - Flame proof motor
- RD - Reduced dimensions

15



15-RD



15-DC



15 SS



25-P



25-S



45



45-CRP



45-FM



75-S



75-SS



75-P



75-CRP



75-FM



TECHNICAL SPECIFICATIONS

Diaphragm type compressors / Vacuum pumps

MODEL	MAX. FLOW RATE (LITRES PER MIN.)	MAX.VACUUM (mm.hg / inches)	MAX.PRESSURE (PSIg)	APPX.WEIGHT (KG)	MOTOR (HP)	APPX. DIMENSIONS (mm)
15	15	22"	25	2.7	1/20	175*110*140
15-RD	15	22"	25	2.5	1/20	150*110*140
15-DC	15	22"	25	3.5	1/20	230*110*150
15 -SS	10	22"	10	5	1/20	185*120*150
25-S	15	27"	35	4.1	1/16	220*110*140
25-P	25	22"	25	4.2	1/16	220*120*140
45	45	22"	35	6.2	1/8	220*120*180
45-CRP	28	22"	10	5.8	1/8	235*155*200
45-FM	35	22"	20	18	1/4	325*150*250
75-P	75	22"	40	9	1/4	290*120*180
75-CRP	38	22"	10	8.7	1/4	325*155*200
75-SS	28	28"	10	8.5	1/4	320*150*230
75-S	45	27"	55	9	1/4	290*120*180
75-FM	75	22"	40	20	1/4	400*150*250

Applications :

Pharmaceutical laboratories / Flame photometry / Diamond cutting machines

Medical equipment - Neonatal ventilators / suction machines / Nebulisers etc.

TS-DVP-2024 Dentistry / / Atomic absorption spectrophotometers / Gold refining